

	FILTER MODEL	COMPONENTS	THICKNESS	INITIAL RESISTANCE TO AIR FLOW	ARRESTANCE EFFICIENCY	DUST HOLDING CAPACITY	UL CLASS	WARRANTY
PREVENT EQUIPMENT PROTECTION	Model U1	PREVENT® EQUIPMENT PROTECTION FILTER 1 Layer Polypropylene Media Flexible Vinyl Edge	1/8"	0.02 in. w.g.	42%	67 grams	Class 2	5 Years
	Model U2	PREVENT® EQUIPMENT PROTECTION FILTER 2 Layers Polypropylene Media Flexible Vinyl Edge	1/8"	0.05 in. w.g.	72%	100 grams	Class 2	5 Years
	Model BHA	PREVENT® EQUIPMENT PROTECTION FILTER 1 Layer Polypropylene High Abrasion Media Flexible Vinyl Edge	1/8"	N/A	N/A	N/A	Class 2	5 Years
	Model R1	PREVENT® EQUIPMENT PROTECTION FILTER 1 Layer Polypropylene Media Rigid Galvanized Steel Frame	1/8"-1/4"	0.02 in. w.g.	42%	67 grams	Class 1 or 2	5 Years
	Model R2	PREVENT® EQUIPMENT PROTECTION FILTER 2 Layers Polypropylene Media Rigid Galvanized Steel Frame	1/8"-1/4"	0.05 in. w.g.	72%	100 grams	Class 1 or 2	5 Years
	WASHABLE COMMERCIAL	Model IN	WASHABLE ELECTROSTATIC FILTER Polypropylene Media & Wire Reinforcement Accumulator Chamber® Design Galvanized or Stainless Steel Frame	1/2", 1", 2"	1"-0.11 in. w.g.	78%	130 grams	Class 1
Model HFA		WASHABLE ELECTROSTATIC FILTER Polypropylene & Non Woven Polyester Media Accumulator Chamber® Design Galvanized or Stainless Steel Frame	1/4", 1/2", 1", 2"	1"-0.20 in. w.g.	89%	120 grams	Class 2	5 Years
Model MME		MIST ELIMINATOR METAL MESH FILTER 12 Layers bonded & corrugated aluminum .017-019 1 Piece aluminum frame Wire Reinforcement Maximum temperature 425° up to 20 Minutes	1" 2"	0.05 in. w.g. 0.06 in. w.g.	N/A	N/A	Class 1	5 Years
METAL MESH	Model MMA	ALUMINUM METAL MESH FILTER 5 Layers of corrugated aluminum mesh Wire Reinforcement Aluminum roll formed frame Maximum temperature 240°	1/2", 1", 2"	1"-0.03 in. w.g. 2"-0.04 in. w.g.	N/A	N/A	Class 1	5 Years
	Model MMS	STAINLESS STEEL METAL MESH FILTER Maximum temperature 900°	1", 2"	1"-0.07 in. w.g.	N/A	N/A	Class 1	5 Years
	Model MMG	GALVANIZED STEEL METAL MESH FILTER Maximum temperature 425°	1" 2"	0.05 in. w.g.	N/A	N/A	Class 1	5 Years
	Model MMH	HEAVY DUTY ALUMINUM METAL MESH FILTER Maximum temperature 275°	1" 2"	0.077 in. w.g.	N/A	N/A	Class 1	5 Years
	Model RH	ALUMINUM RANGEHOOD/APPLIANCE FILTERS Multiple layers bonded aluminum media & frame	1/8"-1/2"	0.06 in. w.g.	N/A	N/A	Class 1	5 Years
	WASHABLE	Model FFA Model FFG	20 PPI WASHABLE FOAM FILTER Aluminum Frame & Mesh Reinforcement Galvanized Steel Frame & Mesh Reinforcement	1/4", 1/2", 1"	1"-0.13 in. w.g.	N/A	N/A	Class 2
Model PFLO1524 Model PFLO2025		POLYESTER RIGID PAD - HOGS HAIR ALTERNATIVE 15" x 24" Pad - Needs No Frame 20" x 25" Pad - Needs No Frame Bi-directional air flow - cleans easily with water	1/2" 1"	0.03 in. w.g. 0.09 in. w.g.	69% 84%	359 grams 229 grams	Class 2 & FMV302	Disposable Disposable