



Aluminum Air Filter Media


Washable metal mesh filter media that can be used in residential, commercial, or industrial applications.

20 gauge corrugated aluminum is a single layer of aluminum mesh that has been pleated into .125", .25" or .625" heights. Flat aluminum mesh is the same media as corrugated, only in it's original flat form. Bonded aluminum, available in .25" or .625" thicknesses, is a flat media that contains several layers of aluminum slit mesh bonded together to create different densities with hundreds of baffle-like surfaces.



MODEL # ALUM.25-19"
MODEL # ALUM.25-24"
MODEL # ALUM.25-40"
MODEL # ALUM.625-19"
MODEL # ALUM.625-24"
MODEL # ALUM.625-40"

- Light in weight and resists corrosion
- Available in custom sized pads or 19", 24" or 40" wide service rolls
- Maximum Temperature: 240°
- U/L Classified as to Flammability Only



MODEL # ALUMCOR.125-19"
MODEL # ALUMCOR.125-24"
MODEL # ALUMCOR.25-19"
MODEL # ALUMCOR.625-24"

MODEL # ALUMMESHFLAT-19"
MODEL # ALUMMESHFLAT-24"

MEDIA	THICKNESS	ROLL SIZE
CORRUGATED	.125"	19.5" X 178' OR 24.5" X 178'
CORRUGATED	.25"	19.5" X 146' OR 24.5" X 146'
CORRUGATED	.625"	24.5" X 100'
FLAT MESH	FLAT	19.125" X 200' OR 24.5" X 200'
BONDED	.25"	19.5" X 50' OR 24.5" X 50' OR 40" X 50'
BONDED	.625"	19.5" X 50' OR 24.5" X 50' OR 40" X 50'

www.permatron.com

1-800-882-8012